

Wood Welded®

Durakryl 102

Oil Finish

Acrylic	Oil
Top/bottom and all edges are sealed.	Top/bottom and all edges are oiled.
Finish not absorbed by carton material.	Oil finish is absorbed into carton material, may result in top drying out and splitting on glue lines.
Does not raise grain.	Raises grain.
Appearance – clear – satin smooth – low sheen – natural in color, consistent, no noticeable light or dark areas, with exception to wood itself.	Appearance – depending on type of oil used may result in darker color of wood. Lack of finish can produce a whitish or unfinished appearance.
Smooth to the touch – no wetness or rough feeling.	Slightly rough (not smooth) to the touch – may have wetness to the touch in areas that do not absorb oil properly. May become sticky depending on type of oil used.
No maintenance required.	Continual maintenance required, weekly, even daily depending on use. Various oils are avail-
Finish will not change chemically once applied and cured – no odor.	Oil finish may go rancid (spoil) give off odor.
Cleanability – wipe as you would any counter surface, soap and water will remove dirt – stains can be removed with bleach or finger nail polish remover. Neither of these will hurt the finish. Anti-bacterial soap can be used, scouring powder will remove stains, but will have a dulling effect on the sheen.	Cleanability – oiled tops have an attraction for dirt and stains, water marks. Water should never be left standing on oiled tops as it will be absorbed into the wood – raise grain, possibly over long period of time, cause glue line to break down. Stains may possibly be removed by bleach – if not – sanding is the only means of removal. Scouring powder will leave a white area. Any heavy cleaning on top will require new application of oil.
If not used as a true cutting surface, the tops will remain beautiful for many years to come.	Oiled tops always look used – simply because they require so much time for maintenance.